

Data sheet

IGNITE ION STRAP





GENERAL

Art. no.:	G-AUS-1135-M/XXL	E-class number:	40-02-01-02
EAN:	4030281247999	Customs no.:	63079098



Data sheet

IGNITE ION STRAP

Our new all-round safety harness for all classical applications in construction and maintenance has above all one major feature due to simplified adjustment options in the chest and leg area as well as three different sizes: exceptional fit! Even for users who rarely wear personal protective equipment against falls from height, the IGNITE ION is extremely easy to use and self-explanatory.

Features two Fall Arrest attachement points. An alloy rear (Dorsal) & Webbing loops (Sternal) at the chest.

The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the webbing during movement and overcome the need for readjusting during work.

User-friendly, self-explanatory, safe:

- · easy to put on and adjust
- · Alloy rear (Dorsal) attachement point
- · large webbing Fall Arrest loops (chest) with wear indicator
- · Adjustable Confined Space loops

GENERAL

Internat. standard: AS/NZS 1891.1:2007

FEATURES

Temperature:

0		
(· ()	\cap	r.
\sim	IV U	ι.

black / orange / anthracite		
Fall indicator		
Shoulder or leg padding:	yes	
Belt strap coiler:	yes	
Hand-washing:	40 °C	
Click buckles:	yes	
Max. service life:	10 Years	
Max. number of persons:	1	
Rated load:	140 KG	
Attachment Points:		
dorsal attachment point, sternal attachment point, rescue eyelet		

from 45 °C to -35 °C



DIMENSIONS

Size:	M/XXL
Waist size:	80-110cm
Weight:	1,51 kg

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Polyester

Rescue eyelet material: Polyester

Dorsal attachment point material:

Aluminium

Material Click buckle: Stainless Steel

