

## Data sheet

# SKYSAFE PRO ADJUSTABLE I



## GENERAL

Art. no.:	L-AUS-0583
EAN:	4030281241300

E-class number:	40-02-01-04
Customs no.:	56090000

## Data sheet

# SKYSAFE PRO ADJUSTABLE I

### GENERAL

Internat. standard: AS 1891.5:2020

50 - 140 kg WITHIN the standard!

The popular SKYSAFE PRO, now also available in a length-adjustable version!

Revolutionary, patented absorber system, which guarantees a max. impact of under 6 kN and a max. fall arrest distance of 1.75 m, even for a broad weight range of 50 - 140 kg. This makes SKYLOTEC the only manufacturer to fulfil the EN 355 standard with an increased test weight of 140 kg and it has also been tested for use on lifting platforms.

Another feature of the absorber, the final impact resistance of 22 kN before AND after a fall is exceptional. The SKYSAFE PRO also meets the most relevant international standards in a SINGLE product.

The SKYSAFE PRO adjustable version completes the SKYLOTEC range of I-web, Y-web, I-web tie-back, Y-web tie-back with a length-adjustable version, which always ensures the optimum distance for your work.

### FEATURES

Colour:	orange
Fall indicator	
Diameter:	25,00 mm
Hand-washing:	40 °C
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	140 KG
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND

## DIMENSIONS

Size:	1,2m - 1,8m
Weight:	1,07 kg

## HARDWARE

Carabiner on anchoring point side:  
KOBRA TRI

## MATERIAL

Material:	Polyester, Polyamide, Steel
Webbing material:	Polyester, Polyamide