

SPHERE

An outstanding 180° field of vision. Easy to fit with its height and width-adjustable headgear and headband, SPHERE adapts to all head shapes for all uses.



Complete head shield and head gear with clear visor
Ref. 1652501

OPTIONAL

Clear replacement visor
Ref. 1652513

Hard hat attachment (hard hat and visor not included)
Ref. 1652518

Head Gear Replacement
Ref. 1652525


355g

- + ULTRA WRAP-AROUND FIT**
- + ADJUSTABLE HEADGEAR**
- + PROTECTION FROM ELECTRICAL SHORT CIRCUIT ARCS**
- + 20.5 X 39.4 CM PC SHIELD**
- + TILTING SHIELD**
- + RESISTANT TO HIGH ENERGY IMPACT (120M/S)**
- + SPLASH PROTECTION**

bolle
SAFETY

SPHERE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SPHERE	 Complete head shield and head gear with clear visor	1652501	V, O	AS/NZS 1337.1.2010	-

LENS MARKING

- V.** The letter 'V' signifies 'High Impact' resistance.
- O.** The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear).

APPLICATIONS

- Chemical splash protection
- Cutting/grinding
- Spraying
- Flash protection
- Acid and alkaline handling
- Wood and metal work
- Brush cutters/chainsaws

MAIN MARKETS

- Petro Chemical
- Construction
- Manufacturing
- Paint
- Automotive
- Labs

LENSES

- 2mm polycarbonate
- 9 base curve
- 100% UV 385 – Clear

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **b-CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact and chemical splash protection. Resists a 6mm at 45 m/s.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC + PVC
STRAP	Non Applicable
FOAM	SBR
SPARE LENSES	No

29/06/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY