

# RUSH+ SMALL

## SPORTY DESIGN, SMALLER FIT

The RUSH+ SMALL adopts all the features of the popular Rush+ model just in a smaller fit. An ultra-sporty design with its co-injected and ultra-flexible temples.

 PLATINUM®

NEW 2019



RUSH+ SMALL : Clear Lens



RUSH+ SMALL : Smoke Lens



RUSH+ SMALL : CSP Lens



1672301 : Clear Lens



1672302 : Smoke Lens



1672310 : Twilight Lens



26 g



Adjustable PVC nose bridge.

- + BUILT IN BROW PROTECTION
- +  PLATINUM COATING (  )
- + ULTRA LIGHT WEIGHT, 9 BASE
- + ADJUSTABLE PVC NOSE BRIDGE
- + CO-MOULDED TEMPLE ARMS FOR COMFORT & GRIP

**bollé**  
SAFETY

# RUSH+ SMALL

## SPORTY DESIGN, SMALLER FIT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>RUSH+ SMALL</b>	 Clear	1672301 	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P
	 Smoke	1672302 	I3 & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P
	 Twilight	1672310 	I2 & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P
	 Clear	RUSHSPSPIS 	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P
	 Smoke	RUSHSPSPFG 	I3 & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P
	 CSP	RUSHPSCSPL 	I1 & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum P

### LENS MARKING

**P.** Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m<sup>2</sup>), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

**I.** The letter 'I' signifies 'Medium Impact' approval.

**O.** The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

### OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear)
- 1.** Range of luminous transmittance 43 -88% (CSP)
- 2.** Range of luminous transmittance 18-43% (Twilight)
- 3.** Range of luminous transmittance 8 -18% (smoke)

### APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory

### MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food industry

### TECHNOLOGIES

#### PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

#### B CSP

This innovative coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that effectively combats fogging.

#### B TWILIGHT

Designed and used in low light conditions, B-Twilight technology improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. B-Twilight filters 76% of blue light.

### LENSES

- 2mm polycarbonate
- 9 base curve
- Platinum coating on both side of clear, smoke, Twilight and CSP lenses
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke, Twilight and CSP

### FRAME MARKING

**AS/NZS 1337.1.2010** : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

29/07/2019

### ASIA/PACIFIC HEADQUARTERS:

Bollé Safety AU Pty Limited  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

[bollesafety.com.au](http://bollesafety.com.au)

### NEW ZEALAND:

T.: 0800 2655 369  
E: bolle@bolle.co.nz

**bolle**  
SAFETY