

# X-GUARD Black Nitrile Gloves

## Intended Use

X-GUARD Black Nitrile Gloves are suited for use across the automotive, industrial, building, coatings & mining sectors. They can be used as a disposable or reusable glove depending on the context of use.

Trade Name	Materials	Type	Colour	UOM
X-GUARD Black Nitrile Gloves	100% Nitrile	Powder free, silicon free, non-sterile, ambidextrous, 270mm length. Flocked lining.	Black	50 gloves
Surface Finish	Shelf Life	Storage Condition		
Fully textured	The gloves shall have shelf life of 5 years from the date of manufacture with the below storage conditions.	The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight, intense artificial light, x-ray machine, heat, moisture and other source of ozone.		

## Glove Standard



EN374-1:2016  
TYPE B  
KPTO



ISO 374-5:2016  
VIRUS

## Part No.

Small	180001
Medium	180002
Large	180003
Extra Large	180004
XX Large	180005

Dimensions	Size	Palm width	Length (mm)
Millimetres (Inches)	Small	88 ± 4mm (3.46" ± 0.16")	270 (minimum) (10.6")
	Medium	100 ± 4mm (3.93" ± 0.16")	270 (minimum) (10.6")
	Large	110 ± 4mm (4.33" ± 0.16")	270 (minimum) (10.6")
	Extra Large	117 ± 4mm (4.60" ± 0.16")	270 (minimum) (10.6")
	XX Large	125 ± 4mm (4.92" ± 0.16")	270 (minimum) (10.6")

Thickness	Palm	Finger
Millimetres	>0.21mm	>0.20mm

Physical Properties	Un-Aged Spec	Aged Spec
Force of Break (N)	Min 14	Min 14
Elongation (%)	Min 500	Min 400



## Packaging Configuration & Labelling

Packaging	50 gloves per inner box (by weight) 10 boxes per outer carton.
Labelling	The inner boxes and outer cartons have the following information: Product description, brand, size, and net quantity of gloves. Country of origin, name and address of distributor, and single use only symbol.